



www.omegaint.com.au/apco | (02) 9832 0000 | 13-27 Melbourne Rd, Riverstone NSW 2765



PRODUCT INFORMATION

ID	A-CHBL1L
Name	Chalkboard Paint
Description	Our premium Chalkboard paint is a water-based finish that will turn virtually any interior paintable surface into a chalkboard. It allows you to create a unique surface that can be written on with chalk.

SURFACE PREPARATION

Remove all dirt, dust and grease from the bare surface. Mould or fungus should be washed with a commercially available mould remover and the affected area may be treated with anti fungus solution. Fill cracks and imperfections with a suitable filler and spot prime. If the surface has been previously painted, remove all flaking or blistered paint completely. Sand all surfaces with 180-grit sandpaper to reduce previous film to a flat finish. For new Plaster and Plasterboard, use APCO Primer.

APPLICATION

Brush, Roller or Spray. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220-grit sandpaper. Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. Do not over roll as glancing light may affect the finished surface. Please use the method best suited to your requirement and skill. The use of asynthetic sleeve of 8 - 10 mm nap on a smooth surface is recommended. For airless spray application, optimum pressure of 2800 psi and nozzle size of 0.015-0.017 inches is suggested as guideline.

PROPERTIES

Gloss	7% - 12%
Tools	Brush, roller, spray
Clean up	Water
Sizes	1L
Colour	Black

Dry time	Touch dry 30 mins Recoat 2 - 4 hours
Coverage	Up to 12m ² /L. Practical coverage may depend on surface profile, method of application and losses.

VOC	<1g/L
Volume Solids	50.8%
Film build at 16 m ² p/L	Dry 40µm Wet 80µm

Thinning Not recommended unless spraying; Up to 5% of water may be added.

Care and Maintenance Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Safety and First Aid Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water. In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.