



www.omegaint.com.au/apco | (02) 9832 0000 | 13-27 Melbourne Rd, Riverstone NSW 2765



ID

Name

Description

PRODUCT INFORMATION

A-EWL15L, A-EWS15L, A-EWG15L, A-EDL15L, A-EDS15L, A-EDG15L, A-EUDL15L, A-EUDS15L, A-EUDG15L, A-EBL15L, A-EBS15L, A-EBG15L, A-EAL15L, A-EAS15L, A-EAG15L

Exterior Paint

Our Exterior paint is a premium self-priming, 100% acrylic water based low sheen finish for exterior use on concrete, cement, bare timber, brick, fibre-cement board, masonry and galvanized iron. The product is easy to apply, has excellent coverage and low dirt pickup. Self-priming in most cases and quick drying. Water wash up for your paint equipment and no harsh solvent odour. Superior Mould Resistance and Life Time Guarantee*

SURFACE PREPARATION

Use our Primer if you are painting over bare plasterboard, masonry, render, cement sheet, brick, MDF, and interior timber. Remove all dirt, dust and grease from the bare surface. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution. Fill cracks and imperfections with a suitable filler and spot prime. All previously painted surfaces should be sanded to remove loose/flaking paint and to reduce previous film to a flat finish.

APPLICATION

Brush, Roller or Spray. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220-grit sandpaper. Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. When applying by spray application, back roll when wet to eliminate plaster set joint smooth setting. Do not over roll as glancing light may affect the finished surface.

PROPERTIES

Gloss 3-8%
Tools Brush, roller, spray
Clean up Water
Sizes 1L, 4L, 10L
Colour White

Dry time Touch dry 30 mins
Recoat 2 hours
Coverage Up to 16m²/L. Practical coverage may depend on surface profile, method of application and losses.

VOC <1g/L
Volume Solids 46%
Film build at 16 m² p/L Dry 17µm
Wet 63µm

Thinning Not recommended unless spraying; Up to 10% of water may be added.

Care and Maintenance Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Warranty See omega.com.au/apco for full warranty statement.

Safety and First Aid Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water. In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.



www.omegaint.com.au/apco | (02) 9832 0000 | 13-27 Melbourne Rd, Riverstone NSW 2765



PRODUCT INFORMATION

ID	A-IWL, A-IWS, A-IWG, A-IDL, A-IDS, A-IDG, A-IUDL, A-IUDS, A-IUDG, A-IBL, A-IBS, A-IBG, A-IAL, A-IAS, A-IAG
Name	Interior Paint
Description	Our premium low VOC wall paint is a hardwearing low sheen finish having excellent flow and levelling. Ideal for use in all living areas, bedrooms and hallways. The product is easy to apply and results in an easy to maintain highly washable finish. Contains anti-fungicidal additives for mould resistance.

SURFACE PREPARATION

Use our Primer if you are painting over bare plasterboard, masonry, render, cement sheet, brick, MDF, and interior timber. Remove all dirt, dust and grease from the bare surface. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution. Fill cracks and imperfections with a suitable filler and spot prime. All previously painted surfaces should be sanded to remove loose/flaking paint and to reduce previous film to a flat finish.

APPLICATION

Brush, Roller or Spray. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220-grit sandpaper. Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. When applying by spray application, back roll when wet to eliminate plaster set joint smooth setting. Do not over roll as glancing light may affect the finished surface.

PROPERTIES

Gloss	3-8%	Dry time	Touch dry 30 mins Recoat 2 hours	VOC	<1g/L
Tools	Brush, roller, spray	Coverage	Up to 16m ² /L. Practical coverage may depend on surface profile, method of application and losses.	Volume Solids	37%
Clean up	Water			Film build at 16 m² p/L	Dry 17µm Wet 63µm
Sizes	1L, 4L, 10L				
Colour	White				

Thinning Not recommended unless spraying; Up to 10% of water may be added.

Care and Maintenance Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Warranty See omega.com.au/apco for full warranty statement.

Safety and First Aid Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water. In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.



www.omegaint.com.au/apco | (02) 9832 0000 | 13-27 Melbourne Rd, Riverstone NSW 2765



PRODUCT INFORMATION

ID	A-TW
Name	Trim Paint
Description	Our trim paint is a premium interior/exterior enamel. It is easy to apply, dries within 30 minutes without an unpleasant odour. Formulated to have a superior flow and provides wear resistant, non-yellowing film. Ideally used for doors, trim/skirting, architraves, furniture and other high contact areas.

SURFACE PREPARATION

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply our primer. For best results on exterior substrates such as timber, brick, blockwork, and compressed fibre cement sheet it is recommended to use our primer. Screen reader support enabled.

APPLICATION

Brush, Roller or Spray. Please use the method best suited to your requirement and skill. Use of a synthetic sleeve of 5mm nap on a smooth surface is recommended. For airless spray application, optimum pressure of 2200 psi and nozzle size of 0.011-0.013 is suggested as guideline. Refer to the spray unit's instruction manual for setting requirements and application method. Note: Do not over brush or over roll when painting, enamel is quick drying and over working the product may not give the desired finish. Paint in cooler temperatures and not in direct sunlight or wind.

PROPERTIES

Gloss 35-40%
Tools Brush, roller, spray
Clean up Water
Sizes 1L, 4L, 10L
Colour White

Dry time Touch dry 30 mins
Recoat 2 hours
Coverage Up to 16m²/L. Practical coverage may depend on surface profile, method of application and losses.

VOC <53g/L
Volume Solids 38%
Film build at 16 m² p/L Dry 22µm
Wet 63µm

Thinning Not recommended unless spraying; Up to 10% of water may be added.

Care and Maintenance Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Safety and First Aid Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water. In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.