

Rustblock Fish Oil

Production Description

Omega Rustblock Fish Oil is a deodorised transparent anti rust protective coating designed to prevent the corrosion of all metal substrates. Rustblock Fish Oil has the capability to penetrate and protect inaccessible rust prone areas such as joints, cracks, side panels, sills and other metal areas and prevents further rusting. Rustblock Fish Oil forms a protective coating on metal and steel surfaces and penetrates rust scale to remove moisture and prevent further corrosion.

Areas of Application

Exterior and Interior applications Rustblock Fish Oil is an anti-corrosive protective fluid for rusted steel where normal surface preparation is difficult. Ideal for hard to reach areas such as cracks, crevices along pipes, nuts and bolts, hinges and welds. Note: Rustblock Fish Oil does not dissolve rust. For badly rusted areas, apply Omega Rustblock Rust Converter.

Technical Data

| | |
|----------------------------------|---|
| Colour | Transparent |
| Solvent Resistance | Not applicable. |
| Toxicity | Do not drink or inhale, keep out of reach of children. |
| Thinning & Clean Up | Clean up with Omega General Purpose Thinner. Do not thin product. |
| Theoretical Coverage* | 12 sq.m. / litre depends on surface profile |
| Drying Time (at 25 C & RH 60%)** | Semi dry: 48 hours ** / Recoat: Not recommended to be painted** |
| Flammable | Keep away from heat and flame, eliminate any source of ignition. |
| Packs available | 1 litre, 4 litre, 300g Spray Pack (other sizes on request) |

*Practical coverage depends on surface profile, method of application and dry film thickness. Higher film thickness leads to lower coverage.

** Cooler temperature, higher film thickness, or higher humidity conditions will lead to longer drying times.

Method of Application

Brush, Spray or Roller. Please use the method best suited to your requirement and skill. Apply 1-2 coats depending on the condition of the area to be protected. Apply sufficient amounts of Rustblock Fish Oil to completely saturate the surface and penetrate well into all crevices. Do not overcoat.

Surface Preparation

Remove all surface rust, loose and flaking / peeling paint and sand back coating edges. Ensure surface is clean, dry and free from dust, grease, oil and all other surface contamination. Apply Omega Rustblock Fish Oil evenly to rust effected areas.

Application

Stir contents thoroughly using a flat stirrer before and during use. Apply one or two coats evenly by brush, roller or spray, after proper surface preparation. Avoid over-brushing and over rolling Rustblock Fish Oil, leave on surface to form a protective film. Not recommended to be over coated. Do not apply to wet or damp surfaces, moisture trapped beneath the Fish Oil film will cause rust and corrosion.

Note: Cooler temperature, higher film thickness, or higher humidity conditions will lead to longer drying times Do not apply when surface temperature is below 10⁰ C or over 35⁰ C

Rustblock Fish Oil

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2, Flash Point 32⁰ C, UN 1263, PG III
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Environmental

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.
- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Safety & Precautions

- Do not apply when surface temperature is below 10⁰ C or over 35⁰ C
- Do not apply in environments of high humidity/moisture, or if pending rain is a possibility.
- Apply in calm fine weather conditions and only during daylight hours.
- Cease painting 2 hours before sunset or if weather changes are forecast.
- Use only the recommended thinner for dilution and cleaning.
- Check paint colour to the colour chart/standard prior to application
- Provide adequate ventilation during use.
- Keep out of reach of children
- Avoid exposure of the new paint film to steam for 48 hours and to washing or scrubbing for 7 days.
- Check cross cut adhesion test of old coating before repainting.
- Apply a test sample for compatibility of this product over a small test area.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone NSW 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed Nov 2018