



**AUSTRALIAN  
PAINT COMPANY**®

**PRO  
SERIES**



## EZI COVER CEILING FLAT

### Production Description

Premium quality acrylic water based, minimal odour, high opacity ceiling paint. Low splatter formulation that dries to an ultra-flat finish. Designed to provide high opacity cover on all living area ceilings. It is easy to apply, non-yellowing and quick drying. Ideal for use in areas with high illumination, excellent for hiding surface imperfections. . May be applied by brush, roller or spray. Contain anti fungicidal additives and may be tinted to a range of colours, and is environmentally friendly, non-toxic, nonhazardous and non-flammable.

### Areas of Application

Sealed and primed or previously painted plasterboard ceilings, set plaster, concrete, plaster, cement render, timber and hardboard.

*For interior use only. Not recommended for use on walls.*

### Technical Data

Colour Range	White and pastel colours
Sheen Level at 60°C head	Flat 0% - 3%
Solvent Resistance	Being thermoplastic film sensitive towards alcohol & aromatic hydrocarbons
Toxicity	Dry film is not toxic
Thinning & Clean Up	Water
Thinning Rate	Up to 10% thinner may be necessary depending on method of application and climatic conditions.
Theoretical Coverage**	9-12 sq. m. / litre per coat. Practical coverage may depend on surface profile, method of application and losses.
Drying Time (at 25C & RH 60%)*	Touch dry: 30 minutes* / Recoat: 2- 4 hours*
Packs available	20L,15L,10L, 4L,
Complies to APAS Standard	APAS 0280/1

\*Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

\*\*Practical coverage may depend on surface profile, method of application and losses. Higher film thickness will lead to lower coverage.

### Method of Application

Brush, Roller or Spray. Please use the method best suited to your requirement and skill. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220- grit sandpaper. Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. When applying by spray application, back roll when wet to eliminate plaster set joint smooth setting. Do not over roll as glancing light may affect the finished surface.

## Australian Paint Company Pty Ltd

### SYDNEY

13-27 Melbourne Road, Riverstone NSW 2765

P: (02) 9832 0000

### BRISBANE

444 Newman Road, Geebung QLD 4034

P: (07) 3265 7890

E: [info@apccoatings.com.au](mailto:info@apccoatings.com.au)

[www.apccoatings.com.au](http://www.apccoatings.com.au)



**AUSTRALIAN  
PAINT COMPANY**®

**PRO  
SERIES**



### Surface Preparation

Remove all dirt, dust and grease from the bare surface. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution. Fill cracks and imperfections with a suitable filler and spot prime. All previously painted surfaces should be sanded to remove loose/flaking paint and to reduce previous film to a flat finish.  
New Woodwork, Plywood, Hardboard: Use Sureprep Acrylic Sealer Undercoat  
New Plaster and Plasterboard: Use Sureprep Acrylic Sealer Undercoat

## EZI COVER CEILING FLAT

### Mix and Colour Check

Mix the paint before application with a wide flat (25mm) paddle or a hand paint mixer with a perforated base, in a circular lifting motion from the bottom of the container for 5 minutes or until the paint and colour are thoroughly mixed. Remix the paint every 2 hours to ensure product consistency.  
Check colour to the colour chart/standard prior to application. Inner mix multiple containers together to ensure colour consistency. Replace and secure container lid during painting to prevent the paint drying within the container.

### Coating Maintenance

Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

### Flammability & Transport Information

- Non-flammable.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

### Environmental

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.
- Refer to state / local EPA and council web sites for environmental and safe disposal details.

### Safety & Precautions

## Australian Paint Company Pty Ltd

### SYDNEY

13-27 Melbourne Road, Riverstone NSW 2765  
P: (02) 9832 0000

### BRISBANE

444 Newman Road, Geebung QLD 4034  
P: (07) 3265 7890

E: [info@apccoatings.com.au](mailto:info@apccoatings.com.au)  
[www.apccoatings.com.au](http://www.apccoatings.com.au)



**AUSTRALIAN  
PAINT COMPANY**®

**PRO  
SERIES**



- Do not apply when surface temperature is below 10<sup>0</sup> C or over 35<sup>0</sup> C
- Do not apply in environments of high humidity/moisture, or if pending rain is a possibility.
- Apply in calm fine weather conditions and only during daylight hours.
- Cease painting 2 hours before sunset or if weather changes are forecast.
- Use only the recommended thinner for dilution and cleaning.
- Check paint colour to the colour chart/standard prior to application
- Provide adequate ventilation during use.
- Keep out of reach of children
- Avoid exposure of the new paint film to steam for 48 hours and to washing or scrubbing for 7 days.
- Check cross cut adhesion test of old coating before repainting.
- Apply a test sample for compatibility of this product over a small test area.
- Always refer to SDS prior to commencement of application.

APCO Coatings 13-27 Melbourne Road Riverstone NSW 2765 Phone (02) 9832 0000 /  
[info@apccoatings.com.au](mailto:info@apccoatings.com.au)  
Reviewed June 2019

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

## **Australian Paint Company Pty Ltd**

### **SYDNEY**

13-27 Melbourne Road, Riverstone NSW 2765  
P: (02) 9832 0000

### **BRISBANE**

444 Newman Road, Geebung QLD 4034  
P: (07) 3265 7890

E: [info@apccoatings.com.au](mailto:info@apccoatings.com.au)  
[www.apccoatings.com.au](http://www.apccoatings.com.au)