



www.omegaint.com.au/apco | (02) 9832 0000 | 13-27 Melbourne Rd, Riverstone NSW 2765



ID

PRODUCT INFORMATION

A-EWL15L, A-EWS15L, A-EWG15L, A-EDL15L, A-EDS15L, A-EDG15L, A-EUDL15L, A-EUDS15L, A-EUDG15L, A-EBL15L, A-EBS15L, A-EBG15L, A-EAL15L, A-EAS15L, A-EAG15L

Name

Exterior Paint

Description

Our Exterior paint is a premium self-priming, 100% acrylic water based low sheen finish for exterior use on concrete, cement, bare timber, brick, fibre-cement board, masonry and galvanized iron. The product is easy to apply, has excellent coverage and low dirt pickup. Self-priming in most cases and quick drying. Water wash up for your paint equipment and no harsh solvent odour. Superior Mould Resistance and Life Time Guarantee*

SURFACE PREPARATION

Use our Primer if you are painting over bare plasterboard, masonry, render, cement sheet, brick, MDF, and interior timber. Remove all dirt, dust and grease from the bare surface. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution. Fill cracks and imperfections with a suitable filler and spot prime. All previously painted surfaces should be sanded to remove loose/flaking paint and to reduce previous film to a flat finish.

APPLICATION

Brush, Roller or Spray. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220-grit sandpaper. Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. When applying by spray application, back roll when wet to eliminate plaster set joint smooth setting. Do not over roll as glancing light may affect the finished surface.

PROPERTIES

Gloss 3-8%
Tools Brush, roller, spray
Clean up Water
Sizes 1L, 4L, 10L
Colour White

Dry time Touch dry 30 mins
 Recoat 2 hours
Coverage Up to 16m²/L. Practical coverage may depend on surface profile, method of application and losses.

VOC <1g/L
Volume Solids 46%
Film build at 16 m² p/L Dry 17µm
 Wet 63µm

Thinning Not recommended unless spraying; Up to 10% of water may be added.

Care and Maintenance Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Warranty See omega.com.au/apco for full warranty statement.

Safety and First Aid Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water. In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.