



www.omegaint.com.au/apco | (02) 9832 0000 | 13-27 Melbourne Rd, Riverstone NSW 2765



PRODUCT INFORMATION

ID	A-P
Name	Primer Paint
Description	Our primer is easy to apply, easy to sand, fights mould, covers well and doesn't smell – perfect for priming, sealing and preparing interior and exterior spaces.

SURFACE PREPARATION

Use our primer if you are painting over the following— bare plasterboard, masonry, render, cement sheet, brick, MDF, and interior timber. Also use Prep paint on pre-painted surfaces that have marks, high gloss surfaces or a darker colour. When painting over a high gloss surface we recommend giving it a quick sand and clean to prep the surface before priming. If you have a repaired patched on your wall you can spot prime over these with a brush, feathering out the edges.

APPLICATION

- Don't apply if ambient temperature is under 10°C or above 30°C or if conditions will drop below 10°C during the drying period
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended
- Stir thoroughly before and during application
- Apply 2 coats by brush, roller or spray

PROPERTIES

Gloss 20-25%
Tools Brush, roller, spray
Clean up Water
Sizes 1L, 4L, 10L
Colour White

Dry time Touch dry 30 mins
 Recoat 2 hours
Coverage Up to 16m²/L. Practical coverage may depend on surface profile, method of application and losses.

VOC <1g/L
Volume Solids 35%
Film build at 16 m² p/L Dry 22µm
 Wet 63µm

Thinning Not recommended unless spraying; Up to 10% of water may be added.

Care and Maintenance Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Safety and First Aid Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water. In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.