



www.omegaint.com.au/apco | (02) 9832 0000 | 13-27 Melbourne Rd, Riverstone NSW 2765



PRODUCT INFORMATION

ID	A-TW
Name	Trim Paint
Description	Our trim paint is a premium interior/exterior enamel. It is easy to apply, dries within 30 minutes without an unpleasant odour. Formulated to have a superior flow and provides wear resistant, non-yellowing film. Ideally used for doors, trim/skirting, architraves, furniture and other high contact areas.

SURFACE PREPARATION

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply our primer. For best results on exterior substrates such as timber, brick, blockwork, and compressed fibre cement sheet it is recommended to use our primer. Screen reader support enabled.

APPLICATION

Brush, Roller or Spray. Please use the method best suited to your requirement and skill. Use of a synthetic sleeve of 5mm nap on a smooth surface is recommended. For airless spray application, optimum pressure of 2200 psi and nozzle size of 0.011-0.013 is suggested as guideline. Refer to the spray unit's instruction manual for setting requirements and application method. Note: Do not over brush or over roll when painting, enamel is quick drying and over working the product may not give the desired finish. Paint in cooler temperatures and not in direct sunlight or wind.

PROPERTIES

Gloss 35-40%
Tools Brush, roller, spray
Clean up Water
Sizes 1L, 4L, 10L
Colour White

Dry time Touch dry 30 mins
Recoat 2 hours
Coverage Up to 16m²/L. Practical coverage may depend on surface profile, method of application and losses.

VOC <53g/L
Volume Solids 38%
Film build at 16 m² p/L Dry 22µm
Wet 63µm

Thinning Not recommended unless spraying; Up to 10% of water may be added.

Care and Maintenance Washing the painted surface periodically will maintain the look of a newly painted surface longer. Clean the surface with a diluted sugar soap or a mild detergent and rinse well with clean water. Do not use scouring pads, abrasive brushes, high pressure washing or solvent to clean the painted surface. These will damage the paint film and cause premature failure of the coating.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Safety and First Aid Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water. In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.