



AUTO ACE

Product/Technical Data Sheet (TDS)

Fish Oil

PRODUCT DESCRIPTION:

Omega Fish Oil is a deodorised, long lasting, rust inhibiting coating suitable for automotive, marine, household, and industrial applications. Fish Oil Compound penetrates through rust and inhibits further corrosion. Intended as a sole coating and does not require a topcoat. Primarily used to inhibit corrosion on surfaces that are already rusted. Often used where preparation for normal anticorrosive paint systems is impractical. Particularly useful in enclosed areas that are difficult to access. Penetrates seams and crevices. Ideal inside automotive panels such as front guards and quarter panels, wheel arches, doors, sill panels. Suitable for trucks, trailers, tractors, and machinery. Do not apply over existing exterior painted surfaces that can be repaired with standard refinishing techniques.

DIRECTIONS FOR USE: SURFACE PREPARATION:

Remove loose rust, flaking paint and all surface dirt with a wire brush, scraper, or sandpaper. Access to sealed areas such as auto doors, stills, etc may be obtained by drilling holes. These should be plugged after application.

APPLICATION:

Apply fish oil Compound liberally dipping, brushing, or spraying. An extension nozzle may be required for hard-to-reach areas. Rusted areas should be saturated to ensure Fish Oil penetrates to the base metal. Metal that is relatively rust free requires only a thin coating.

SETTING: Allow approx. 48 hours drying. Notes: Fish Oil does not dry to a hard surface. Surfaces subject to exposure to the elements should be re-coated at regular intervals.

CLEAN UP: Clean up with Omega Wax & Grease Remover.

STORAGE: Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight.

DISPOSAL: Dispose of in accordance with local, state and federal regulations.

RISK: FLAMMABLE. Harmful by inhalation and in contact with the skin and eyes. Vapours may cause drowsiness or dizziness.



AUTO ACE

SAFETY DIRECTIONS: DO NOT SWALLOW. Use in a well-ventilated area. Avoid contact with skin and eyes. Wear gloves and safety glasses. Rags, paper, sawdust and other combustible materials contaminated with Fish Oil may self-ignite causing fire. Soak these items in water immediately after use. Dispose of in a water filled sealed metal container.

Standard packages and Product Codes

1LT – AA-FO1L

400G – AAFO400G