

01. PREPARE

Remove rust, paint and surface contaminants.

Technical Data Sheet:



09.2021



Product Details:

Product Name:	Omega Auto Ace Fast-Strip
Product Group:	Step 1 Prepare
Product Description:	Omega Fast Strip is a fast acting heavy bodied automotive and industrial strength paint remover formulated to rapidly strip automotive paints (including 2 pack) from concrete, glass, masonry, metals, and timber.

Directions For Use:

Substrates: 	Metal, Concrete, Glass, Masonry, Timber.
Surface Preparation: 	Roughly remove any excess build up or dirt, grease, and oil from the surface to be stripped. Protect any adjacent materials which may be sensitive to stripper, e.g., mask or remove plastic, rubber, vinyl or fabric trim from the area to be stripped. Briefly scouring the painted surface with coarse sandpaper may help speed the stripping action.

Directions For Use:**Application:**

Shake the can well before use. Apply a thick even coat by brush or roller and allow approximately 15 minutes to 1 hour for the old paint to soften, blister and/or wrinkle. Polyurethane and Two Pack Acrylic Urethane coating may take longer. Remove loosened paint by scraping and clear away residue with a cloth. Wipe over with Omega Pro-Flow General Purpose Thinners to thoroughly clean the surface and remove any remaining paint residue. Collect stripper and paint residue into a container for disposal. Occasionally a second application may be necessary.

Aerosol Application:

Shake can well before use. Spray on a medium/heavy even coat and allow approximately 15 minutes to 1 hour for the old paint to soften, blister and/or wrinkle. Polyurethane and Two Pack Acrylic Urethane coating may take longer. Remove loosened paint by scraping and clear away residue with a cloth. Wipe over with Omega Pro-Flow General Purpose Thinners to thoroughly clean the surface and remove any remaining paint residue. Collect stripper and paint residue into a container for disposal. Occasionally a second application may be necessary.

Turn can upside down and spray briefly to clear nozzle after use.

Additional Information	
Clean Up:	Wash down with water to remove most of the residues. A wash down with a strong thinner such as acrylic or multipurpose thinners may be useful in removing the remaining paint residues
Storage:	Store upright in a cool, dry, well-ventilated area. Always replace the lid securely after use.
Disposal:	Dispose of in accordance with local, state, and federal regulations
Risk:	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May damage fertility or the unborn child. May cause respiratory irritation. Toxic to aquatic life with long lasting effects
Safety Directions:	Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. Collect spillage.

Standard Packaging:		
Product Code:	Product Size:	Product Colour:
AA-FS1L	1LT	Translucent Paste/Gel
AA-FS4L	4LT	Translucent Paste/Gel
AA-FS400G	400G (Aerosol)	Translucent Paste/Gel

Disclaimer: In lieu of all warranties expressed or implied, the seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable for any injury, loss, damage, direct or consequential, arising out of the use of or inability to use this product. Since the use and application of this product is beyond the control of the seller and the manufacturer, the purchaser and user assume all risk and liability whatsoever, in connection with this product therewith. Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2