

OMEGA 2K Polyurethane Thinner

Production Description

OMEGA 2K Polyurethane Thinner is formulated specially for spray applications of 2 pack polyurethane systems.

Areas of Application

Recommended to be used as thinner or clean-up solvent for 2 pack polyurethane systems. Also suitable for high performance acrylic finishes, protective lacquers and automotive varnishes.

Technical Data

Appearance	Low viscosity, colourless clear liquid
Specific Gravity	0.85
Boiling Range	56-130 °C
Thinning Recommendations	Addition of 10-20% may be used, depending on product type and application equipment.
Packs available	4 litres and 20 litres

Flammability & Transport

- Highly flammable, Dangerous Goods Class 3.2.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.

Safety & Precautions

Refer to SDS for detail instructions.

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed Jul 2021