

Cuprinat Wood Preserver

Production Description

Cuprinat Wood Preserver is a unique composition of copper salt and petroleum hydrocarbon specially formulated to protect the timber from rot and termite attack. It is deep penetrating, water repellent. The solution is easy to apply by brush or roller.

Areas of Application

The product is recommended for timber decks, garden furniture, timber fence etc., and it is suitable for interior and exterior use.

Technical Data

Colour	Green
Solvent Resistance	N/A
Toxicity	Dry film is nontoxic
Thinning & Clean Up	Enamel Thinner/ Mineral turps. Hits product is designed for undiluted application. However up to 5% thinner can be used if necessary.
Theoretical Coverage*	4 - 6 sq.m. / litre per coat, depends on surface profile*
Drying Time (at 25 C & RH 60%) **	Touch dry in 20 minutes / Recoat after 2-4 hours**
Gloss Level	N/A
Packs available	4 litres and 20 litres

*Practical coverage depends on surface profile, method of application and dry film thickness. Higher film thickness leads to lower coverage.

** Cooler temperature, higher film thickness, or higher humidity conditions will lead to longer drying times.

Method of Application

Brush or foam Roller. Please use the method best suited to your requirement and skill.
Not recommended for spraying, maybe used in a dip tank application.

Surface Preparation

Remove all the dust, dirt, grease and oil from the surface. If any mould or fungus is present on the surface, treat it with commercially available bleaching agent and then wash with water thoroughly. Allow complete drying.

Application

Stir the contents thoroughly before use. Apply one coat of Cuprinat Wood Preserver and allow it to get soaked into the timber. Apply second coat by allowing the first coat to dry for 2-4 hours. Generally, two or three coats are sufficient. Do not apply when surface temperature is below 10° C or over 35° C. Do not apply in environments of high humidity/moisture, or if pending rain is possibility.

Flammability & Transport

- Highly Flammable.
- Keep away from heat and flame, eliminate any source of ignition.
- Soak all used cloths and rags immediately in water to prevent self-ignition.
- Ensure container is upright with lid secure.
- Ensure the container is secured in the vehicle for transport.



Australian Made & Australian Owned



Cuprinat Wood Preserver

Environmental

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.
- Refer to state / local EPA and council web sites for environmental and safe disposal details.

Safety & Precautions

- Do not apply when surface temperature is below 10 °C
- Use only the recommended thinner for dilution and cleaning.
- Provide adequate ventilation during use.
- Please refer to the Material Safety Data sheet before using the product.
- Keep out of reach of children
- Check crosscut adhesion test of old coating before recoating.

Disclaimer: In lieu of all warranties expressed or implied, the seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable for any injury, loss, damage, direct or consequential, arising out of the use of or inability to use this product. Since the use and application of this product is beyond the control of the seller and the manufacturer, the purchaser and user assume all risk and liability whatsoever, in connection with this product therewith.

Omega Paints Pty Ltd., 13-27 Melbourne Road Riverstone 2765 Phone (02) 9832 0000 /

info@omegapaints.com.au

Reviewed April 2021