

# ΩMEGA®

AUTO ACE

**PRESSURISED CONTAINER:** Do not pierce or burn, even after use, keep away from sources of ignition. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F.

**FIRST AID:** For advice, contact a Poisons Information Centre (e.g. Phone Australia 131 126, New Zealand 0800 764 766) or a doctor. If swallowed, do NOT induce vomiting. If in the eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by Poisons Information Centre or a doctor or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If medical advice is needed have product container or label at hand.

**KEEP OUT OF REACH OF CHILDREN.**

**EXTREMELY FLAMMABLE:**

Do not use near fire or flame.

**BEWARE:**

Deliberately sniffing or inhaling concentrated spray can be harmful or fatal.

**STORAGE & DISPOSAL:**

Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight. Dispose of in accordance with local, state, and federal regulations.

# RUST CONVERTER

RUST CONVERTER PRIMER & SEALER  
TRANSFORM RUST INTO A PAINTABLE SURFACE

**Omega Rust Converter Primer & Sealer** is a tannic acid-based rust converter that converts rust to a black stable primed finish preventing further corrosion. It can be primed, filled and painted over to give additional corrosion proofing or sound dead-ending. It is suitable to treat rust in all areas where Omega Rust Remover is recommended and is ideal for use in inaccessible areas and for tools and components that are usually not primed or rust proofed.

**DIRECTIONS FOR USE**

**SURFACE PREPARATION:** Remove loose rust, flaking paint and mill scale by using power tool or hand tool eg wire brush. Wash the surface to remove all traces of wax, grease, silicone, oil, salt, mould, mild dew, dust and dirt. Allow to dry before applying Rust Converter. Mask off surrounding areas to avoid over painting.

**APPLICATION:** Shake can vigorously for 1 minute after the sound of the agitator is heard. Spray in an even, overlapping pattern from a distance of approximately 25cm. Apply to dry surfaces only. Do not apply to hot surfaces. Avoid if possible application in direct sunshine. The rusted areas of the surface will turn predominantly black. Only apply to rusted surfaces-not a rust preventative for clean steel.

**FINISHING:** Suitable for use under most paint systems. May be left up to 3 months before priming and top coating. With single pack paints allow minimum drying 3 hours at 20°C before applying primers or topcoats. For 2 pack paints allow 24 hours drying at 20°C.

**CLEAN UP:** Use Omega Pro Flow Multi-Purpose Thinner.  
**SAFETY DIRECTIONS:** Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/ protective clothing/ eye protection/face protection. Collect spillage. Causes serious eye and skin irritation. May cause an allergic skin reaction. May damage fertility or the unborn child. May cause respiratory irritation. Toxic to aquatic life with long lasting effects.

**PRODUCT CODE:**

AA-RCP400G

For further information refer to the Material Safety Data Sheet or contact Omega Industries +61 2 9832 0000

Omega Industries Pty Ltd  
13-27 Melbourne Rd  
Riverstone NSW 2765 Australia  
[www.omegaid.com.au/autoace](http://www.omegaid.com.au/autoace)

**CONTAINS:** Butyl Glycol Ether 2-4%



**DANGER**

**HAZARD STATEMENTS:** Extremely flammable aerosol. Causes serious eye and skin irritation. Harmful if swallowed, in contact with skin or if inhaled.

**IMPORTANT:** Deliberate misuse of this aerosol to damage property is a crime.

**PROPELLANT:**  
DIMETHYL ETHER  
10-30%

# 1

**STEP ONE**  
400g NET

UN. 1950 AEROSOLS