



AUTO ACE

Product/Technical Data Sheet (TDS)

ACETONE

PRODUCT DESCRIPTION:

Omega Acetone is a premium grade solvent suitable for cleaning surfaces prior to application. Omega Acetone is also ideal for removing Fibreglass Resin and paint from tools, brushes and for removing body filler and fibreglass filler from mixing boards, applicators etc.

BEFORE USE: Testing on small areas is always recommended prior to application to determine suitability as certain plastics and painted on lacquered surfaces can be damaged.

APPLICATION: Use directly from can to avoid contamination. Pour onto cloth and apply liberally to area to be cleaned. Only clean small area at any one time.

STORAGE: Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight.

DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

RISK: HIGHLY FLAMMABLE: Harmful if swallowed. Irritating to eyes, respiratory system, and skin.

SAFETY DIRECTIONS: Avoid contact with the skin and eyes and avoid breathing in the vapour. Wear suitable protective clothing, gloves, and eye protection. Keep away from sources of ignition – **NO SMOKING**. Use in a well-ventilated area. **DO NOT SWALLOW**.

Standard packages and Product Codes

500ML – AA-AC500ML