



AUTO ACE

Product/Technical Data Sheet (TDS)

Acrylic Primer Surfacer

PRODUCT DESCRIPTION:

Omega Acrylic Primer Surfacer is a light grey single pack, fast drying, easy sanding automotive primer, suitable for priming over bare steel, body filler, nitrocellulose stop putty, finishing putty, fibreglass repairs, and sound existing paintwork. Features excellent adhesion, filling properties, smooth levelling, fast drying and easy to sand.

DIRECTIONS FOR USE: SURFACE PREPARATION:

For maximum adhesion, spray bare steel with Omega Etch Primer first, then apply Omega Primer Surfacer. Prepare the surface by removing all rust and flaking paint by grinding or sanding. Treat bare metal with Omega Rust Remover & Deoxidiser. Ensure the surface to be painted is free from wax, grease, silicon, oil, and dirt by thoroughly cleaning with Omega Wax & Grease Remover, Mask off surrounding areas to avoid overspray.

APPLICATION:

Thoroughly stir contents, use a suction or gravity feed spray gun and thin at a ratio of 1 part Primer 1 to ½ parts Omega PRO-FLOW Thinner. Spray 2-3 medium coats with 5-10 minutes drying time between coats. Allow to dry for a minimum of 4 hours at 20°C or preferably overnight before sanding with 600-800 grit paper. Allow longer in cool weather and where high film build has been applied. Finally apply acrylic lacquer topcoat.

AEROSOL APPLICATION:

Shake can vigorously for one minute after the sound of agitator is heard. Spray in an even, overlapping pattern from approximately 25cm. Apply several light coats leaving five minutes drying time between coats. Turn the can upside down and spray briefly to clear the nozzle after use.

DRY & RECOAT: Touch dry in approx. 15 minutes. Hard dry 24 hours Recoat after 24 hours. Based on 20°C and 50% relative humidity. Allow more time at cooler temperatures.

CLEANUP: Use Omega Pro-Flow Multi- Purpose Thinner.

STORAGE: Store upright in a cool, dry, well ventilated away from heat, ignition sources and direct sunlight. Always replace the lid securely after use.

DISPOSAL: Dispose of in accordance with local, state, and federal regulations. Do not empty into drains.



AUTO ACE

RISK: HIGHLY FLAMMABLE: This package contains highly volatile and flammable solvents and when using contents, adequate ventilation to the outside must be provided. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches) must be eliminated in or near the working area – **NO SMOKING.**

SAFETY DIRECTIONS: Avoid contact with skin and eyes and avoid breathing in the vapour. Irritating to skin.

FIRST AID: For advice, contact a Poisons Information Centre (e.g. Phone Australia 131 26, New Zealand 0800 764 766) or a doctor. If swallowed, do NOT induce vomiting. If in the eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Standard packages and Product Codes

1LT – AA-APSG1L

2LT – AA-APSG2L

400G – AA-APSG400G