



AUTO ACE

Product/Technical Data Sheet (TDS)

Contact Adhesive

PRODUCT DESCRIPTION:

Omega Contact Adhesive is an easy-to-use rapid set, high initial strength adhesive ideal for automotive and marine use. Suitable for bonding a wide variety of surfaces. Including vinyl, leather, paper, cardboard, prints, photographs, artwork, wood, fabric, plastics, metal and much more. Suitable for porous and non-porous surfaces.

DIRECTIONS FOR USE:

Use only on clean dry surface free from dirt, dust, oil, grease, and other contaminants. Use Omega Wax & Grease Remover to clean non-porous surfaces.

APPLICATION:

Sample testing of a small non-critical area is advisable when product is used on unfamiliar surfaces. Apply a thin coating to both surfaces to be bonded. For porous surfaces two or more coats may be required. Wait until the adhesive had touch dried – about 15 minutes. Press the surfaces together firmly, ensuring that they are accurately lined up. Full strength achieved at 24 hours.

CLEAN UP: Use Omega Pro Flow Multi-Purpose Thinner.

STORAGE: Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight.

DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

RISK: HIGHLY FLAMMABLE. Harmful if swallowed, by inhalation and in contact with the skin. Irritating to eyes, skin, and respiratory tract.



AUTO ACE

SAFETY DIRECTIONS: Avoid contact with the skin and eyes and avoid breathing the vapour. Keep away from sources of ignition – **NO SMOKING**. Use in a well-ventilated area. Do not empty into drains. Store in a cool dry place. Always replace lid securely after use.

Standard packages and Product Codes

500ML – AA-CA500ML

400G – AA-CA400G