



**AUTO ACE**

# Product/Technical Data Sheet (TDS)

## Plastic Primer

### **PRODUCT DESCRIPTION:**

Omega Plastic Primer is a clear, single pack primer designed to bond automotive acrylic lacquers, single pack enamels and 2 pack automotive paints to polypropylene and polyolefin plastics and bumper bars. The clear base reduces the number of topcoats required to restore or match the surrounding finish.

### **DIRECTIONS FOR USE: SURFACE PREPARATION:**

Prepare the surface by thoroughly cleaning and degreasing with Omega Wax & Grease Remover. Follow by carefully abrading with Scotch Brite Hand Pad (Grey) or equivalent. Care must be taken not to damage plastics. Once again clean and degrease with Omega Wax and Grease Remover. Mask off surrounding areas to avoid overspray.

### **APPLICATION:**

Shake vigorously for 1 minute after the sound of the agitator is heard. Spray in an even, overlapping pattern from a distance of approximately 25cm. Apply two light coats allowing for a flash-off time of 5-10 minutes between coats. Allow to dry for 15-20 minutes before applying the next coat. Turn the can upside down and spray briefly to clear the nozzle after use. For the next step apply the selected topcoat.

**CLEAN UP:** Use Omega Pro-Flow Thinners.

**STORAGE:** Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight.

**DISPOSAL:** Aerosols should be completely empty before disposing. Dispose of in accordance with local, state, and federal regulations.



**AUTO ACE**

**RISK: EXTREMELY FLAMMABLE.** Harmful by inhalation and in contact with skin. Irritating to skin.

**SAFETY DIRECTIONS: KEEP OUT OF REACH OF CHILDREN.** Avoid contact with the skin and eyes and avoid breathing the vapour. **WARNING** – Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. **DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING. PRESSURISED DISPENSER. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN, EVEN AFTER USE. SPRAY IN WELL VENTILATED AREA.**

**Standard packages and Product Codes**

AEROSOL – AA-PP400G