



AUTO ACE

Product/Technical Data Sheet (TDS)

Rust Inhibitor

PRODUCT DESCRIPTION:

OMEGA Rust Inhibitor is a heavy-duty wax coating for rust and corrosion prevention. It dries to a flexible, non-sticky, water repellent film. Designed for use on concealed internal surfaces of cars, trucks, trailers, caravans, 4-wheel drive and off-road vehicles, tractors and farm machinery, equipment, and tools. It will inhibit the formation of rust inside internal box sections, chassis, door cavities, sills, side panels and pillars.

DIRECTIONS FOR USE; SURFACE PREPARATION:

All surfaces to be coated should be rust free, dry, and clean. Clean accessible surfaces with Omega Wax & Grease Remover. Mask off surrounding areas to avoid over spray.

APPLICATION:

Sound deadener gun attaches directly to the can. Use standard spray tip for accessible areas. A flexible tube attachment for the body deadener gun will allow internal sections to be coated. Apply 2 coats allowing 15 minutes drying between coats. Spray at pressure of approximately 40 psi depending on flow rate required. Pressure may be varied to obtain the desired flow and textured effect. Apply 2 coats allowing 15 minutes flash off time between coats.

DRYING TIME: Allow to dry for approximately 4 hours at 20°C. Allow longer at lower temperature and for higher film thickness. Overnight drying is recommended before plugs and seals are replaced.

CLEAN UP: Clean up with Omega Wax & Grease Remover.

STORAGE: Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight.



AUTO ACE

DISPOSAL: Aerosols should be completely empty before disposing. Dispose of in accordance with local, state and federal regulations.

RISK: EXTREMELY FLAMMABLE. Harmful by inhalation and in contact with skin. Irritating to skin.

SAFETY DIRECTIONS: KEEP OUT OF REACH OF CHILDREN. Avoid contact with the skin and eyes and avoid breathing the vapour. **WARNING** – Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. **DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING. PRESSURED DISPENSER. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN, EVEN AFTER USE. SPRAY IN WELL VENTILATED AREA.**

Standard packages and Product Codes

1.15LT – AA-CRI1L

400G – AA-CRI400G