



**AUTO ACE**

## Product/Technical Data Sheet (TDS)

# Stone Guard Water Based

### **PRODUCT DESCRIPTION:**

Omega Stone Guard is a water based flexible textured underbody coating for protection against stone chips and general road abrasion. Ideal for use in the repair of underbody areas such as sills, wheel arches, and front and rear aprons.

### **DIRECTIONS FOR USE: SURFACE PREPARATION:**

Remove all rust, dirt, and flaking paint. Grind or sand the surface with coarse paper to promote adhesion. Wipe over thoroughly with Omega Wax & Grease Remover to ensure that the surface is clean, dry, and free of oil, grease, wax, and any other contaminants.

### **APPLICATION:**

Shake can well before use and apply with an “underbody” gun directly out of the can or by brush or roller. Apply only to primed or previously painted surfaces. Apply 2-3 coats allowing 10 minutes air flash between coats. Do not apply at temperatures less than 15°C. Clean all equipment immediately after use with water. Do not coat functional parts such as springs, exhaust, driveshafts, engine, etc.

**DRYING TIME:** Finish will be touch dry in approximately 2 hours at 25°C or less if used in a low bake oven system at 60°C. Heavy coatings and low temperature will extend drying times. When dry can be overpainted with refinishing paint systems.

**CLEAN UP:** Residues may be washed away with water.

**STORAGE:** Store upright in a cool, dry, well ventilated area away from heat, ignition sources and direct sunlight. Always replace the lid securely after use.

**DISPOSAL:** Dispose of in accordance with local, state, and federal regulations.

**SPILLS/LEAKS:** Wash all spills and leaks with water.

### **Standard packages and Product Codes**

BLACK 1.15LT – AA-SGWB1L