



Product Data Sheet

Apco Acekote

Product Description:

Apco AceKote is a premium 100% acrylic water based paint engineered specifically for tennis courts and multi-sport surfaces. This high-performance coating delivers a uniform, non-slip finish thanks to its advanced formulation incorporating specially graded mineral fillers. AceKote provides exceptional durability, ensuring long-lasting protection against wear and tear from intense gameplay. Its unique composition offers players excellent traction and consistent ball bounce, enhancing the overall playing experience. Suitable for various surfaces including concrete and asphalt, AceKote is UV-stable and resistant to weathering, making it ideal for both indoor and outdoor applications. With its easy application process and quick drying time, AceKote allows for efficient court resurfacing and maintenance, minimizing downtime.

Key Features:

- High Performance Coating
- Non-slip Finish
- Exceptional Durability

Areas Of Use:

Suitable for concrete and asphalt surfaces.

Technical Data:

Colours: White, Black, Yellow, Blue, Red

Location: Interior/Exterior

Gloss Level: Matt

Thinning: Water up to 10%

Application: Spray, Brush, Roller

Pack Size: 15L

Coverage:

Theoretical Coverage 5m²/ Litre. Practical coverage may depend on surface profile and method of application.

Preparation:

Before applying Apco Acekote, ensure the surface is thoroughly cleaned and free from all loosely adhered material. For old asphalt courts, level and clean the surface. New asphalt courts should cure for at least 28 days before painting. New concrete courts require a minimum 28 day curing period, and acid etching may be necessary. When repainting old surfaces, remove all loose paint, clean with a detergent solution, and rinse thoroughly with clean water. Allow the surface to dry completely before coating. If water beads on any area during rinsing, it indicates contamination that may affect paint adhesion. For unknown coatings, test adhesion and compatibility on a small area before proceeding. Additionally, ensure all surfaces are free of oil, dirt, grease, and other contaminants. Fill any cracks and holes prior to application.

Application:

Apply two coats to a dry surface with 4-6 hours drying time between coats. For application using a roller, a short nap roller is recommended to ensure a smooth even surface, apply even downward pressure to avoid leaving thick film sections. Spread the paint evenly, maintaining a wet edge, and allow the first coat to dry completely. Inspect the surface and remove any excess lumps or irregularities before applying the second coat. For spray applications up to 10% water may be necessary depending on climate conditions.

Do not over brush or over roll when painting, AceKote Tennis Court Coating is quick drying and over working the product may not give the desired finish.

Do not apply in high humidity or when temperature is below 15°C or above 30°C.

Dry Times: At 25°C

Touch Dry: 30 Minutes

Recoat: 4-6 Hours

Cleaning Of Equipment:

After each use, promptly clean all equipment with water. Ensure that tools and equipment are thoroughly washed before the product has a chance to cure.

Mix and Colour Check:

Mix the paint thoroughly before application using a wide flat paddle or a hand mixer with a perforated base. Mix in a circular lifting motion from the bottom of the container for 5 minutes or until the paint and colour are fully blended. Stir the paint every 2 hours to maintain consistency. Check the colour against the colour chart or standard before applying. For multiple containers, mix them together to ensure colour uniformity. During painting, replace and secure the container lid to prevent the paint from drying out.

Environmental

Do not wash painting equipment and allow waste to enter drains and waterways. Do not dispose of unwanted paint and thinners that will enter drains and waterways. Refer to state / local EPA and council websites for environmental and safe disposal details.

Safety and Precautions:

Read the Safety Data Sheet (SDS) for this product before use. The SDS contains important information on hazards, precautions, personal protective equipment, first aid, and safe handling instructions. To obtain a copy of the SDS, visit our website at www.apcocoatings.com.au or call our customer service line at (02) 9832 0000. Keep out of reach of children. Keep windows and doors open during use and while drying to ensure adequate ventilation. If swallowed, immediately call the Poisons Information Centre at - Australia: 13 11 26, New Zealand: 0800 764 766 or contact a doctor. Avoid contact with skin and eyes.

Disclaimer

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times