



**Product Data Sheet**

# Sports Oval Marking

**Product Description:**

APCO Sports Oval Marking Paint is a premium water-based line marking paint, designed specifically for marking sports ovals with precision and durability. Engineered to meet the demanding needs of athletic fields, with exceptional performance and vividness, ensuring clear and defined lines for various sporting events. Whether you're marking soccer fields, football fields, or any other sports ovals, Apco Sports Oval's water based line marking paint provides professional grade results, meeting the stringent requirements of sports professionals and field maintenance experts. Ensure your sports field stands out with crisp, clear, and enduring lines.

**Key Features:**

- High visibility
- Safe on all grass
- Easy to apply
- Long lasting
- Made in Australia
- Water Based

**Areas Of Use:**

All types of grass sporting fields: Football, Soccer, Baseball, Golf Courses, Bowls, Rugby, Softball, Athletics etc.

**Technical Data:**

Colours:	White, Black, Yellow, Blue, Red
Gloss Level:	Matt
Thinning:	Water up to 10%
Application:	Spray, Roller
Pack Size:	15L

**Coverage:**

Theoretical Coverage 8-10m<sup>2</sup>/ Litre. Practical coverage may depend on surface profile and method of application.

**Preparation:**

Ensure the field is clean, dry, and free from debris such as leaves, grass clippings, and dirt. Begin by mowing the grass to the recommended height and removing any loose material. If the surface is uneven, consider rolling it to create a smooth, level base. Ensure the surface is completely dry before application to promote optimal adhesion and longevity of the paint.

**Application:**

Apco Sports Oval Marking is suitable for spray machines, transfer wheel markers, and roller applications. Mark out the lines accurately using string or a pre-marking tool to ensure precision. Apply the paint evenly along the pre-marked lines, maintaining a steady pace and consistent pressure to ensure uniform coverage. For best visibility, apply one to two coats, allowing sufficient drying time between applications. Finally, allow the paint to dry completely before use, typically 2-4 hours depending on humidity and temperature, to prevent smudging and ensure durability.

Do not apply in high humidity or when temperature is below 10°C or above 30°C.

**Thinning:**

Up to 10% water may be necessary depending on method of application and climatic conditions.

**Dry Times: At 25°C**

Touch Dry:	20 Minutes
Recoat:	2 Hours

**Cleaning Of Equipment:**

After each use, promptly clean all equipment with water. Ensure that tools and equipment are thoroughly washed before the product has a chance to cure.

**Safety and Precautions:**

Read the Safety Data Sheet (SDS) for this product before use. The SDS contains important information on hazards, precautions, personal protective equipment, first aid, and safe handling instructions. To obtain a copy of the SDS, visit our website at [www.apccoatings.com.au](http://www.apccoatings.com.au) or call our customer service line at (02) 9832 0000. Keep out of reach of children. Keep windows and doors open during use and while drying to ensure adequate ventilation. If swallowed, immediately call the Poisons Information Centre at - Australia: 13 11 26, New Zealand: 0800 764 766 or contact a doctor. Avoid contact with skin and eyes.

**Mix and Colour Check:**

Mix the paint thoroughly before application using a wide flat paddle or a hand mixer with a perforated base. Mix in a circular lifting motion from the bottom of the container for 5 minutes or until the paint and colour are fully blended. Stir the paint every 2 hours to maintain consistency. Check the colour against the colour chart or standard before applying. During painting, replace and secure the container lid to prevent the paint from drying out.

**Environmental**

Do not wash painting equipment and allow waste to enter drains and waterways. Do not dispose of unwanted paint and thinners that will enter drains and waterways. Refer to state / local EPA and council websites for environmental and safe disposal details.

**Disclaimer**

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development

The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times