

Product Range Catalogue

PROTECTIVE COATINGS

Developing and supplying professional paint products since 1987.



CONTENT

| | | |
|--------------------------------|---------------------------------|--------|
| Primers | Metal Etch Primer | 04. |
| | Zinc Phosphate Primer | 05. |
| | Red Oxide Primer | 06. |
| | Duratec Self-Primer | 07. |
| Topcoats | Duralume Anti-Corrosive | 08. |
| | Sugar Mill Silver | 09. |
| | Quick Dry Enamel | 10. |
| | AGI Enamel | 11. |
| | Dipping Enamel | 12. |
| | Quick Dry Electrostatic Enamel | 13. |
| | High Build Chlorinated Rubber | 14. |
| | High Temperature Paint | 15. |
| Automotive Coatings | Hammertone | 16. |
| | Chassis Black | 17. |
| Concrete Coatings | Radiator Black | 18. |
| | Concrete Sealer | 19. |
| | Omepoxy Two Pack Flooring Epoxy | 20. |
| Timber Coatings | Omethane Two Pack Polyurethane | 21. |
| | Wood Primer | 22. |
| Solvents & Thinners | Cuprinat Wood Preserver | 23. |
| | Solvents & Thinners | 24-25. |

OUR STORY

From humble beginnings

Established in 1987, the company then known as Omega International Coatings Pty Ltd, was a small light industrial paint company based in Sydney. Its only manufacturing facility was in Mount Drutt, NSW which produced industrial paints, varnishes, and thinners. In 2000, after leaving his role as an Accountant, Kan Shetty found his next opportunity in the

classified section of the Sydney Morning Herald. It read "small paint manufacturing" company for sale. Kan would mix paint and then print labels he made on a word document while his family would glue them on cans to go door to door in industrial complexes to sell paint to industrial fabricators and box trailer assemblers.

Omega International Coatings Pty Ltd continued its exponential growth until 2007 when it acquired Apco Coatings (subsidiary of multinational paint manufacturer Asian Paints), then broadening their scope into automotive, decorative and specialty paints.



ETCH PRIMER

Omega Metal Etch Primer

Omega Metal Etch Primer is a high-performance, ready to use, single-pack etch primer designed to provide exceptional adhesion and outstanding protection on a wide variety of metal surfaces. Omega Metal Etch Primer is ready to use and dries quickly, allowing for fast overcoating with a variety of topcoats.



Key Features:

- Touch Dry in 15 minutes
- Exceptional adhesion
- Ready to use
- Corrosion resistant

Uses:

Omega Metal Etch Primer is ideal for a wide range of metal surface applications, including roofs, gutters, downpipes, metal frames, fences, railings, and gates.

Substrates:

Aluminium, Stainless steel, Mild steel, Galvanised steel, Zinalume, Brass, Copper

Application:

Specifications:



BRUSH



ROLLER



SPRAY



RECOAT



COVERAGE



TOUCH DRY

- O-EPW4L White 4L
- O-EPG4L Grey 4L
- O-EPB4L Black 4L
- O-EPW20L White 20L
- O-EPG20L Grey 20L
- O-EPB20L Black 20L

**Custom colours available on request, minimum order quantities apply.*

ZINC PHOSPHATE PRIMER

Omega Zinc Phosphate Primer

Omega Zinc Phosphate Primer is a single pack, quick-drying anticorrosive industrial primer, enhanced with anticorrosive pigments to ensure superior adhesion and optimal corrosion resistance. Suitable for industrial, marine, and commercial applications. Ideal for steel surfaces where blast cleaning is impractical.



Key Features:

- Easy to sand
- Protects against corrosion
- Excellent adhesion
- Easy application

Uses:

Omega Zinc Phosphate Primer is ideal for a wide range of applications, including structural steel frames & trusses, industrial & marine equipment.

Substrates:

Steel surfaces. Ideal for steel surfaces where blast cleaning is impractical.

Application:

Specifications:



BRUSH



ROLLER



SPRAY



RECOAT



COVERAGE



TOUCH DRY

- O-ZPPLG4L Light Grey 4L
- O-ZPPDG4L Dark Grey 4L
- O-ZPPBK4L Black 4L
- O-ZPPRO4L Red Oxide 4L
- O-ZPPLG20L Light Grey 20L
- O-ZPPDG20L Dark Grey 20L
- O-ZPPBK20L Black 20L
- O-ZPPRO20L Red Oxide 20L

**Custom colours available on request, minimum order quantities apply.*

RED OXIDE PRIMER

Omega Red Oxide Primer

Omega Red Oxide Primer is a single pack, air drying coating based on modified alkyd resin, formulated to provide superior protection for steel surfaces in moderate corrosive environments. Omega Red Oxide Primer has high-quality anticorrosive pigments, providing excellent adhesion and corrosion protection in one coat.



Key Features:

- Hard Wearing
- Rust-Inhibiting
- Excellent Adhesion
- Corrosion Protection

Uses:

Ideal for applications including structural frames and trusses in factories and warehouses, as well as farm equipment, machinery, fences, roofs, doors, pipes, gutters, railings, and gates.

Substrates:

Steel surfaces.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



RECOAT



COVERAGE



TOUCH DRY

O-ROX4L Red Oxide 4L
O-ROX20L Red Oxide 20L

DURATEC SELF-PRIMER

Omega Duratec Self-Primer

Omega Duratec is a high performance protective coating designed for steel surfaces where complete rust removal is challenging. Duratec's fast-drying formula offers exceptional adhesion properties and serves as a self-priming solution with anticorrosive pigments to provide protection against further corrosion. Omega Duratec can be top-coated with Omega QD Industrial Enamel or other oil-based enamels.



Key Features:

- Quick Drying
- Self Priming
- Excellent Adhesion
- Interior & Exterior use

Uses:

Duratec may be used as a standalone finish on structural steel, especially in situations where thorough surface preparation is impractical. It can also be used for touching up of weld joints after removing weld flux. Suitable for interior and exterior use.

Substrates:

Steel surfaces.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



RECOAT



COVERAGE



TOUCH DRY

O-DSP4L Grey 4L
O-DSP20L Grey 20L

DURALUME

Omega Duralume Anti-Corrosive

Omega Duralume is a single-component, fast-drying coating specifically formulated for the restoration of old mild steel and severely weathered galvanised steel. Duralume contains anti-corrosive pigments including aluminium which enhance adhesion and provides excellent corrosion resistance. Additionally, it delivers an aesthetically pleasing appearance similar to that of typical zinc-galvanised finishes.



Key Features:

- Single Component
- Excellent Adhesion
- Fast Drying
- Contains Anti-Corrosive Pigments

Uses:

Recommended for the refurbishment of old mild steel and severely weathered galvanised steel.

Substrates:

Steel Surfaces.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



RECOAT



COVERAGE



TOUCH DRY

O-DAC4L Silver Grey 4L
O-DAC20L Silver Grey 20L

SUGAR MILL SILVER

Omega Sugar Mill Silver

Omega Sugar Mill Silver is a high-performance aluminium paint specifically formulated for use on roofs and structural steel. Sugar Mill Silver offers easy application with a silver gloss finish that has outstanding durability in outdoor environments, suitable for both interior and exterior applications and is also ideal as a general maintenance coating.



Key Features:

- Easy Application
- Premium Finish
- Excellent Durability
- Interior & Exterior use

Uses:

Interior and exterior primed structural steel and roof surfaces. Also recommended as a general purpose maintenance coating.

Substrates:

Primed Steel Surfaces.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



RECOAT



COVERAGE



TOUCH DRY

O-SMS4L Silver 4L
O-SMS20L Silver 20L

QUICK DRY ENAMEL

Omega Quick Dry Enamel

Omega 360 Quick Dry Enamel is a fast drying and economical industrial topcoat designed to protect primed interior and exterior metal surfaces where a durable gloss finish is required. Omega 360 offers excellent flow and gloss properties, making it suitable for a wide range of industrial and commercial applications.



Key Features:

- Quick Drying
- Excellent Durability
- Touch Dry in 15 Minutes
- Quick & Easy Application

Uses:

Recommended for use on all primed metal surfaces including: Shipping containers, Trailers, Fences, Gates, Fabricated steel, Factory equipment and machinery.

Substrates:

Primed Metal Surfaces.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



RECOAT



COVERAGE



TOUCH DRY

O-QDGESW4L Gloss White 4L O-QDEBK4L Gloss Black 4L
O-QDGESW20L Gloss White 20L O-QDEBK20L Gloss Black 20L

Other standard and custom colours available on request.

AGI ENAMEL

Omega AGI Enamel

Omega AGI Enamel is a premium single-pack high gloss coating designed for exterior agricultural application. Omega AGI Enamel provides excellent exterior durability, colour retention, and mechanical resistance to wear, making it ideal for harsh conditions. Omega AGI Enamel's long open time allows for easy application via conventional or airless spraying.



Key Features:

- Excellent Durability
- Good Mechanical Resistance to Wearing
- Excellent Colour Retention
- Long Open Time For Easy Application

Uses:

Omega AGI Enamel is designed for exterior agricultural applications such as cranes, harvesters, truck bodies, etc.

Substrates:

Primed Metal Surfaces.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



RECOAT



COVERAGE



TOUCH DRY

O-WAGIEW4L Gloss White 4L O-WAGIEGB4L Gloss Black 4L
O-WAGIEW20L Gloss White 20L O-WAGIEGB20L Gloss Black 20L

Other standard and custom colours available on request.

DIPPING ENAMEL

Omega Dipping Enamel

Omega Dipping Enamel is a single-pack, quick drying dipping enamel designed for effortless application in dip tanks for all metal articles. This fast-drying formula provides a tough, uniform coating. Available solvent-based and water-based.



Key Features:

- Quick Drying
- Excellent Durability
- Easy Application
- Tough Uniform Coating

Uses:

Omega Dipping Enamel is ideal for challenging items such as coils, tools, springs, pipe scaffolding, and sway bars.

Substrates:

Metal, Steel.

Application:



DIPPING

Specifications:



RECOAT



COVERAGE



TOUCH DRY

ELECTROSTATIC ENAMEL

Omega Quick Dry Electrostatic Enamel

Omega Quick Dry Electrostatic Enamel is a single pack quick drying alkyd-based enamel, formulated for use in electrostatic spraying applications directly from container. It is suitable for most metal or steel surfaces such as machinery, tools, pipes, etc. Requires no on-site adjustments to produce effective electrostatic wrap during application. Excellent adhesion to ferrous surfaces & good durability.



Key Features:

- Excellent Adhesion
- Quick Drying
- Excellent Durability
- Touch Dry 15 Minutes

Uses:

Omega Electrostatic Enamel is ideal for a wide range of applications, including steel tanks, bridges, cranes, wharfs and shore installations, equipment in industrial and marine environments.

Substrates:

Metal & Mild Steel Surfaces.

Application:



SPRAY

Specifications:



RECOAT



COVERAGE



TOUCH DRY

O-QDES20L White 20L O-QDESBK20L Black 20L

Other standard and custom colours available on request.

HIGH BUILD CHLORINATED RUBBER

Omega High Build Chlorinated Rubber

Omega High Build Chlorinated Rubber is an air-drying finish paint that dries quickly and offers excellent flexibility and acid resistance. It is ideal for marine and chemical environments, as well as for use as traffic paint and on metal surfaces.



Key Features:

- Fast Drying
- Excellent Flexibility
- Hardwearing
- Good Chemical Resistance

Uses:

Recommended as a finish coat for protecting structural steel, storage tanks, and pipelines in chemical plants, can also be applied to concrete and masonry surfaces for both interior and exterior use.

Substrates:

Steel, Concrete, & Masonry Surfaces.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



4-6 hrs

RECOAT



10 m²

COVERAGE



15 min

TOUCH DRY

O-CRW4L White 4L O-CRB4L Black 4L
O-CRW20L White 20L O-CRB20L Black 20L

Other standard and custom colours available on request.

HIGH TEMPERATURE PAINT

Omega High Temperature Paint

A single component, high temperature coating based on moisture cure silicon resin. It is suitable for temperature up to 650°C. Provide protection of steel from corrosion on equipment exposed to high temperature like Chimneys, Exhausts, Vents and Pipes.



Key Features:

- Prevents Rust
- Heat Resistant to 650°C
- Satin Finish
- Self-Priming

Uses:

Recommended for equipment that exposed to high temperature including: Pot-Belly Stoves, Heaters, Ovens, Flues, BBQs, Exhaust Manifolds.

Substrates:

Cast Iron, Steel & Stainless Steel.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



12 hour

RECOAT



10 m²

COVERAGE



30 min

TOUCH DRY

O-HIGTB4L Black 4L O-HIGTS4L Silver 4L O-HIGTW4L White 4L
O-HIGTB20L Black 20L O-HIGTS20L Silver 20L O-HIGTW20L White 20L

HAMMERTONE

Omega Hammertone

Omega Hammertone is a quick-dry decorative industrial coating with a hammered metal surface pattern which is ideal for camouflaging surface imperfections with a highly decorative effect. It is a tough durable and anti-corrosive finish with excellent adhesion. When sprayed produces a uniform and attractive hammer pattern with good slip resistance. Omega Hammertone offers a hard and glossy finish.



Key Features:

- Fast Drying
- Hardwearing
- Gloss Finish
- Excellent Chemical Resistance

Uses:

Ideal for use on Trailers, Machinery, Equipment, Fences, Gates, Railings, Windows, Furniture.

Substrates:

Steel, Aluminium, Wrought Iron, Brass Copper, Zincalume, Galvanised Iron, Pre Painted Surfaces.

Application:

Specifications:



BRUSH



ROLLER



SPRAY



RECOAT



COVERAGE



TOUCH DRY

O-HTB4L Black 4L
O-HTB20L Black 20L

O-HTDC4L Dark Charcoal 4L
O-HTDC20L Dark Charcoal 20L

O-HTDB4L Deep Blue 4L
O-HTDB20L Deep Blue 20L

O-HTSA4L Silver Ash 4L
O-HTSA20L Silver Ash 20L

CHASSIS BLACK

Omega Chassis Black

Omega Chassis Black is a single pack, quick drying enamel based on modified alkyd. It is specially designed enamel for automotive chassis to provide excellent weathering properties. No need to apply primer before application of this product.



Key Features:

- Fast Drying
- Hardwearing
- Excellent Adhesion
- Satin Finish

Uses:

Recommended for protection and maintenance of all automotive chassis/subframes.

Substrates:

Steel Surfaces.

Application:

Specifications:



BRUSH



ROLLER



SPRAY



RECOAT



COVERAGE



TOUCH DRY

O-ICB4L Black 4L
O-ICB20L Black 20L

RADIATOR BLACK

Omega Radiator Black

Omega Radiator Black is a single pack rapid drying black paint based on modified alkyd specially formulated for spraying application on radiators to provide protection and decoration of steel surfaces.



Key Features:

- Fast Drying
- Hardwearing
- Gloss Finish
- Excellent Chemical Resistance

Uses:

Specifically formulated for radiators, heater cores and air conditioning condensers.

Substrates:

Steel Surfaces.

Application:



SPRAY

Specifications:



2 hour

RECOAT



8 m²

COVERAGE



2 min

TOUCH DRY

O-IRB20L Black 20L

CONCRETE SEALER

Omega Concrete Sealer

A premium heavy duty solvent based finish designed to protect concrete, brickwork, exposed aggregate, stone, pebbles & masonry. The sealant forms an attractive, protective and impervious coating on the substrate to protect against spillage of common fluids. May also be used to bind loosely bound or aged cement & concrete surfaces. The product is recommended for protection against moderate erosion and dust.



Key Features:

- Fast Drying
- Hardwearing
- Excellent Adhesion
- Satin Finish

Uses:

Ideal for verandahs, courtyards, driveways, and paths.

Substrates:

Stamped & stencilled concrete, exposed aggregate, pebble finishes, brick, sandstone.

Application:



BRUSH



ROLLER



SPRAY

Specifications:



2 hour

RECOAT



10 m²

COVERAGE



15 min

TOUCH DRY

O-ICC4L Clear 4L
O-ICC20L Clear 20L

O-ICCO4L Coloured 4L
O-ICCO20L Coloured 20L

OMEPOXY FLOOR COATING

Omepoxy Two Pack Flooring Epoxy

Omega Omepoxy is a ultra heavy duty hard wearing two pack epoxy gloss coating developed for floors that require the highest level of protection. Omega Omepoxy provides outstanding durability to interior floors and protects against solvents, chemicals, and other industrial fluids.



Key Features:

- Heavy Duty
- Excellent Durability
- Hard Wearing
- Protects Against Oil & Grease

Uses:

Ideal for industrial floors, workshop floors, garage floors & high traffic areas.

Substrates:

Omepoxy can be applied directly on bare concrete surfaces after proper surface preparation has been completed, also suitable as a finish coat on steel structures, pipelines, tankage in marine and chemical environments.

Application:

Specifications:



BRUSH



ROLLER



SPRAY



16-24 hrs

RECOAT



8m²

COVERAGE



6-8 Hrs

TOUCH DRY

OMETHANE FLOOR COATING

Omethane Two Pack Polyurethane

Omega Omethane 343 is an extremely heavy duty Two Pack Polyurethane gloss floor coating. It can be used on interior & exterior floors and provides excellent protection to concrete & timber surfaces. Omethane has been specially developed to provide outstanding durability, gloss, & colour retention.



Key Features:

- Excellent Adhesion
- Heavy Duty
- Excellent Durability
- Interior & Exterior

Uses:

Designed for floors in areas subject to heavy wear, exposure to chemicals, solvents and other industrial fluids.

Substrates:

Omethane can be applied directly on bare concrete, timber, & metal surfaces after proper surface preparation.

Application:

Specifications:



BRUSH



ROLLER



SPRAY



16-24 hrs

RECOAT



12m²

COVERAGE



1-2 Hrs

TOUCH DRY

WOOD PRIMER

Omega Wood Primer

Omega Wood Primer is a high quality quick drying undercoat based on modified alkyd specially formulated for priming timber which is to be top coated with various finishes such as polyurethane coatings. Recommended as a primer for softwoods, hardwoods, chipboard and fibre board. It is suitable for interior and exterior woodwork.



Key Features:

- Quick Drying
- High Film Build
- High Opacity
- Easy to Sand

Uses:

Recommended as a primer for softwoods, hardwoods, chipboard, and fibre board. It is suitable for interior and exterior woodwork.

Substrates:

Softwoods, Hardwoods, Chipboard, Fibre Board.

Application:

Specifications:



BRUSH



ROLLER



SPRAY



16 hour

RECOAT



10 m²

COVERAGE



4 hour

TOUCH DRY

O-WPW4L 4L
O-WPW20L 20L

CUPRINATE WOOD PRESERVER

Omega Cuprinat Wood Preserver

Cuprinat Wood Preserver is a unique composition of copper salt and petroleum hydrocarbon specially formulated to protect the timber from rot and termite attack. It is deep penetrating, water repellent. The solution is easy to apply by brush or roller.



Key Features:

- Easy Application
- Deep Penetration
- Water Repellent
- Excellent Long Term Durability

Uses:

Recommended for timber decks, garden furniture, timber fence etc., and it is suitable for interior and exterior use.

Substrates:

Wood Surfaces.

Application:

Specifications:



BRUSH



ROLLER



DIPPING



6 m²

COVERAGE



20 min

TOUCH DRY

O-CWP4L Transparent Green 4L
O-CWP20L Transparent Green 20L

THINNERS & SOLVENTS

Omega General Purpose Thinner

Omega General Purpose thinner is a premium quality paint thinner formulated specially for spray applications.



Omega Acrylic Thinner

Omega Acrylic Thinner is a formulation of premium quality solvent paint thinner designed for optimal performance to aid flow, gloss and over spray melt-in.



Omega Enamel Thinner

Omega Enamel Thinner is a blend of quick evaporating solvent specially formulated for quick dry enamels, primers and hammertone.



Omega Epoxy Thinner

Blended thinner for reducing 2 Pack Epoxy coatings to a suitable spraying viscosity, provides fast initial flash off allowing for better vertical hold up.



Omega Chlorinated Rubber Thinner

Omega Chlorinated Rubber Thinner is a aromatic hydrocarbon based solvent with moderate evaporation rate.



Omega Polyurethane Thinner

Omega 2K Polyurethane Thinner is formulated specially for spray applications of 2 pack polyurethane systems.



THINNERS & SOLVENTS

Omega Methylated Spirits

Omega Methylated Spirits is a solvent suitable for thinning paints, lacquers, varnishes and also can be used for cleaning paint brushes.



Omega Mineral Turpentine

Omega Paints Mineral turpentine is a slow-evaporating cost effective solvent with good solvency



Omega Acetone

Omega Acetone is a very fast evaporating solvent with great solvency. It is recommended as a thinner for spraying application



Wax & Grease Remover

A highly effective blend of solvent which effectively removes wax, grease, polish, oil, tar, grime, glue and most other contaminants



Omega Gunwash

Solvent blend used to clean spray lines, guns, and other equipment. Universal products suitable for clean-up for single pack and two pack products.



Omega Paint Stripper

Omega Paint Stripper is a heavy-duty paint and coating remover, which is non-flammable, super strong and quick acting.





ΩMEGA®


PROTECTIVE COATINGS

Contact us for more information or visit our website
www.omegaint.com.au | info@omegaint.com.au


Developing and supplying professional paint products since 1987.




Sydney AUSTRALIA
13-27 Melbourne Road
Riverstone NSW 2765
Tel: 02 9832 0000




Dallas USA
4060 Shilling Way
Dallas Texas 75237




Brisbane AUSTRALIA
444 Newman Road
Geebung QLD 4034
Tel: 07 3265 7890



Singapore
22 Benoi Sector
Singapore 629854



Wellington NEW ZEALAND
Omega Industries Pty Ltd
DISTRIBUTOR



Malaysia
Lot no 3414 Block 7
Demak Laut Ind Park
Kuching Sarawak 93050